

REDI ROCK PRODUCTS



Proceeding pages are in LIMESTONE only

Cobblestone



Smooth Face

Limestone

















Limestone	Photo	Specs	Notes
28 Top		8 in. FACE 13 in. 28 in.	-1230 lbs
Freestanding Corner Top		46 ^{1/8} in. 13 in.	-1160 lbs -One long sided face will need to be removed by contractor
Freestanding Corner Half Top		23 1/16 in. 13 in.	-520 lbs -One long sided face will need to be removed by contractor

Limestone	Photo	Specs	Notes
Freestanding Cap		18 in. 46 ^{1/8} in.	-1370 lbs Lift; Lift Loop in one short side
Freestanding Corner Cap		FACE 18 in. 13 in.	-1370 lbs; Lift Loop in one short side
Freestanding Corner Half Cap		18 in. 23 1/16 in. 13 in.	-520 lbs; Lift Loop in one short side

Limestone	Photos	Specs	Notes
28 Middle			-1580 lbs
28 Half Middle		18 in. or 23 1/16 in.	-780 lbs
28 Bottom		18 in. 28 in.	-1680 lbs
41 Middle		18 in. 46 1/8 in.	-2172 lbs
41 Half Middle		18 in. 23 ^{1/16} in.	-1150 lbs
41 Bottom		18 in. 41 in.	-2530 lbs
60 Middle		18 in. 46 1/8 in.	-3330 lbs

Limestone	Photo	Specs	Notes
Freestanding Middle		18 in. 46 ½ in.	-1330 lbs; Small knobs
Freestanding Corner Middle			-1450 lbs; Small knobs
Freestanding Half Corner Middle		FACE 18 in. or 23 1/16 in. 13 in.	-750 lbs; Small knobs

Limestone	Photo	Specs	Notes
2 Sided		6 in. 20 in. 46 ½ in.	-630 lbs
3 Sided		6 in. 20 in. 46 ^{1/8} in.	-630 lbs
4 Sided		6 in. 20 in. 46 1/8 in.	-630 lbs